

## PowerLine Module

GE LAN | RS-485 | DI/DO | Industrial IoT | ITU-T G.hn

### PM-1540, PM-1510

As per ITU-T standards, Comtrend's Power Module series utilizes G.hn technology to provide a wired, secure, bounded latency, high speed, and real-time connection. With Gigabit LAN port(s), RS-485 and DI/DO interfaces, Power Modules can collect and transfer data over power lines from power meters (or EVSE) and IoT devices to replace Ethernet cable wiring/unstable wireless connections of existing field applications. It enables significant cost savings on installation, maintenance and wiring materials.

The Power Module series works within an electric wire domain of up to 250 nodes; enabling large scale deployment, ideal for EV charging station (EVSE) backend communication, smart parking and data centers.

From an installation point of view, the Power Module design provides a terminal block (for power wire insert), mounting holes and a DIN rail mounting kit option.



#### KEY FEATURES

- Data and power on a single wire, reuses existing wiring
- Up to 250 nodes in one power group connection
- Up to 16 levels of repetition
- Reaches up to 600 meters in field tests
- Automatic Self-Healing - node to node will find the best path via software
- Plug and Play

# PM-1540, PM-1510

GE LAN | RS-485 | DI/DO | Industrial IoT | ITU-T G.hn

## SPECIFICATIONS

HARDWARE					
Model	PM-1540	PM-1510	PM-1510PoE	PM-1510dc	PM-1510s
Ethernet Port	4	1	1	1	1
Data In / Data Out	1	1	1	1	Optional
RS-485	1	1	1	1	Optional;
Others	NONE	NONE	PSE/802.3 at 15.4W for Surveillance	(i). SFP as WAN (ii) 12Vdc/1.5A powering gateway	PCB package for integration with 3 <sup>rd</sup> party
DIN Rail Kit	Optional	Optional	Optional	Optional	NONE
*GIGABIT ETHERNET					
IEEE 802.3bz 10/100/1000 BASE-T, auto-sense Support MDI/MDX					
POWER LINE COMMUNICATION					
ITU-T G.9960 & G.9961 compliant G.hn 50MHz MIMO Boost					
MANAGEMENT					
HTTP Web-based (optional) TR-069 over IPv4/v6 dual stack (Optional)					
MODULATIONS					
OFDM, FEC					
DIMENSIONS					
<b>PM-1540, PM-1510, PM-1510PoE, PM-1510dc</b> 115mm (H) x 65 mm (W) x 21 mm (PCB w/components) 120mm (H) x 70 mm (W) x 26.5 mm (with housing)					
<b>PM-1510s</b> 75mm (H) x 75 mm (W) x 21 mm (PCB w/components)					
ENVIRONMENT					
<b>Temperature</b>	Operating: 10°C ~ 70°C (-40°C ~ 70°C as an option) Storage: -25°C ~ 65°C (-13°F ~ 149°F)				
<b>Humidity (Non-condensing)</b>	Operating: 10 ~ 90% RH, non-condensing Storage: 5 ~ 90% RH, non-condensing				
ACCESSORY					
DIN Rail mounting kit (Optional)					



Warning

- Disconnect the PLC from the power source before servicing
- Do NOT open the casing
- For indoor user only
- Do NOT use near water

# COMTREND

**Taiwan:**  
3F-1, No.10, Lane 609, Chongxin Road, Section 5,  
Sanzhong Dist, New Taipei City 241405, Taiwan  
Tel: +886-2-29998261

**USA & Canada:**  
530 Technology Dr. Suite 100, Irvine,  
CA 92618, USA  
Tel: +1-949-753-9640

**Spain:**  
C/ Proci3n, 7 portal 2, 1º C - Edif. Am3rica II  
28023 Madrid, Spain  
Tel: 34-917990403

**Czech Republic:**  
TOKOVO Jankovcova 1518/2, 170 00, Prague 7,  
Czech Republic  
Tel: +420-266-782040

Maximum performance, actual data rates, and coverage will vary depending on network conditions and environmental factors. Product specifications and design are subject to change without notice.