

G.hn Wave2 over Coax Adapter

G.hn 2Gbps | 200MHz | Built-in Diplexer

GCA-6010



GCA-6010 is designed as CPE (customer premises equipment) for Ethernet Adapter over coax network home networking, as well as for MDU application over a shared coaxial network. GCA-6010 fully complies with ITU-T G.hn standards for a coaxial interface and supports a 200MHz operating band and built-in diplexer for coexistence of CATV/UHF/VHF services.

Two coaxial interfaces on the GCA-6010; one is for connecting to the backbone coax network and the other is for the TV set.

KEY FEATURES

- **Super Performance:** With ITU-T G.hn baseband plans, 200MHz for coax up to 2Gbps PHY rate over coax.
- **Ultra High Speed Data Transmission:** Of up to 1.7 Gbps dramatically increases the performance of next-generation home entertainment.
- **Plug & Play:** Allows quick and easy connections with embedded plug-and-play, no extra configuration required. It can be paired easily by simply connecting Ethernet cables to routers and devices.
- **Security:** With advanced data encryption capability, the coax networks are safer and more secure.
- **Diplexer for existence with existing TV service:** Cut-off above 250MHz for existing TV signals, saving the extra cost for deployment.

GCA-6010

G.hn 2Gbps | 200MHz | Built-in Diplexer

SPECIFICATIONS

SPECIFICATIONS	
Interface	<ul style="list-style-type: none">▪ RJ-45 X1 for GE Ethernet▪ LED Indicators: G.hn, Security, LAN, PWR▪ Buttons: G.hn pairing, Reset▪ F-type connector x 2
G.hn (Coax)	<ul style="list-style-type: none">▪ ITU-T G.9960 & G.9961 compliant▪ G.hn 200MHz▪ Link rate 2Gbps,▪ Data throughput 1.7Gbps
Management	<ul style="list-style-type: none">▪ HTTP Web-based▪ TR-069 over IPv4/v6 dual stack
Network Protocols	<ul style="list-style-type: none">▪ 802.1D Ethernet Bridge▪ 802.1Q VLAN▪ Quality of Service (QoS)▪ IGMP(IPv4) Snooping & MLD(IPv6) Snooping
Diplexer for existing TV service	Frequency: 250MHz to 1.2 GHz
External Power Adapter	Input: AC100-240V, Output: DC12V /1A
Dimensions	133mm (D) x 70mm (W) x 38mm (H)
Certifications	CE, FCC, UL, ITU-T G.hn Standard
ENVIRONMENT	
Operating Temperature	0 ~ 40 degrees Celsius
Relative Humidity	8 ~ 95% (non-condensing)

COMTREND

Taiwan:
3F-1, No.10, Lane 609, Chongxin Road, Section 5,
Sanzhong Dist, New Taipei City 241405, Taiwan
Tel: +886-2-29998261

USA & Canada:
530 Technology Dr. Suite 100, Irvine,
CA 92618, USA
Tel: +1-949-753-9640

Spain:
C/ Proci3n, 7 portal 2, 1º C - Edif. Am3rica II
28023 Madrid, Spain
Tel: 34-917990403

Czech Republic:
TOKOVO Jankovcova 1518/2, 170 00, Prague 7,
Czech Republic
Tel: +420-266-782040

Maximum performance, actual data rates, and coverage will vary depending on network conditions and environmental factors. Product specifications and design are subject to change without notice.