

G.hn Wave2 Powerline DC

G.hn 1.2Gbps | 100MHz MIMO | 12VDC/30W

PG-9180dc



The **PowerGrid 9180dc**, ITU-T G.hn networking standard compliant ethernet adapter, provides the best quality data transmission for the truly high-speed 'connected home' experience. It allows users to extend a local area network via existing power lines, eliminating the need for extra wiring. Installation at home (or in a small office) is quick and easy as the PowerGrid 9180dc comes with plug-and-play technology. Additional 12V/30W DC output is provided with CPE power adaptor saving on wall socket usage.

The PowerGrid 9180dc supports the new generation of so-called G.hn wave2 tech, 100MHz MIMO operation and can be used with two fully programmable reception and transmission paths to attain up to 1.2Gbps PHY over powerline. The PowerGrid 9180dc comes pre-configured allowing easy installation / configuration and it features most secure end-to-end encryption algorithms for safeguarding the network integrity with advanced energy-saving features based on Ethernet link activity; automatic standby mode.

KEY FEATURES

- **MIMO Performance:** ITU-T G.hn baseband plans 100 MHz MIMO techniques boosting PLC throughput up to 1.2Gbps PHY rate over powerline.
- **High Speed Data Transmission:** High speed (around max 1000 Mbps) dramatically increases the performance of next-generation home entertainment applications.
- **No Extra Wires Needed:** The local area network can be extended without the hassle of having to install extra wiring because the power line network is already a commonplace fixture in most households.
- **Simple Pairing, Plug & Play:** High speed (around max 1000 Mbps) dramatically increases the performance of next-generation home entertainment applications.
- **Extends Connecting Range & Eliminates Dead Spots:** Unlike wireless, Power line technology is capable of actually covering more than 95% of a typical household area.
- **Security:** With advanced data encryption capability, the power line networks are safer and more secure.
- **12V/30W DC output:** Integrating a CPE power adaptor inside for saving a wall socket, and also saving on the external power supply of a home gateway, wireless AP, STB or IP Camera.

PG-9180dc

G.hn 1.2Gbps | 100MHz MIMO | 12VDC/30W

SPECIFICATIONS

SPECIFICATIONS	
Interfaces	<ul style="list-style-type: none">▪ RJ-45 X 1 for Ethernet connection▪ DC output X 1 for 12Vdc output▪ AC power jack X 1 for AC power cord▪ LED Indicators: G.hn, LAN, PWR, Security▪ Buttons: G.hn pairing, RESET
Ethernet	<ul style="list-style-type: none">▪ Standard IEEE 802.3▪ 10/100/1000 Mbps BaseT auto-sense▪ Auto rate and duplex negotiation▪ MDI/MDX support
G.hn	<ul style="list-style-type: none">▪ ITU-T G.9960 & G.9961 compliant▪ G.hn 100MHz MIMO▪ Up to 1200 M bps at Phy rate▪ NDIM support
Modulations	<ul style="list-style-type: none">▪ OFDM, FEC, Flexible frequency configuration
Management	<ul style="list-style-type: none">▪ HTTP Web-based (optional)▪ TR-069 over IPv4/v6 dual stack (Optional)
Security	<ul style="list-style-type: none">▪ AES 128 bits encryption ensures total data security
Networking Protocols	<ul style="list-style-type: none">▪ 802.1D Ethernet Bridge▪ 802.1Q VLAN▪ Quality of Service (QoS)▪ IGMP(IPv4) Snooping & MLD(IPv6) Snooping
AC Power	<ul style="list-style-type: none">▪ 100-240 VAC, 50Hz/60Hz
DC Power	<ul style="list-style-type: none">▪ 12VDC/30W under 30 degrees Celsius▪ 12VDC/24W under 40 degrees Celsius▪ DC plug: 2.5mm ID x 5.5 mm OD
Dimensions	<ul style="list-style-type: none">▪ 39mm (H) x 72mm (W) x 132 mm (D)
Certifications	<ul style="list-style-type: none">▪ FCC, cUL, CE, ITU-T G.hn Standard <p>Note: Specifications are subject to change without notice.</p>
ENVIRONMENT	
Operating Temperature	0 ~ 40 degrees Celsius
Relative Humidity	0 ~ 95% (non-condensing)



WARNING

Disconnect the PLC from the power source before servicing
For indoor user only
Do NOT open the casing
Do NOT use near water

COMTREND

Taiwan:
3F-1, No.10, Lane 609, Chongxin Road, Section 5,
Sanzhong Dist, New Taipei City 241405, Taiwan
Tel: +886-2-29998261

USA & Canada:
530 Technology Dr. Suite 100, Irvine,
CA 92618, USA
Tel: +1-949-753-9640

Spain:
C/ Proci3n, 7 portal 2, 1º C - Edif. Am3rica II
28023 Madrid, Spain
Tel: 34-917990403

Czech Republic:
TOKOVO Jankovcova 1518/2, 170 00, Prague 7,
Czech Republic
Tel: +420-266-782040