

PowerLine Module

GE LAN | RS-485 | DI/DO | Industrial IoT | ITU-T G.hn

PM-1540

As per ITU-T standards, Comtrend's Power Module series utilizes G.hn technology to provide a wired, secure, bounded latency, high speed, and real-time connection. With Gigabit LANport(s), RS-485 and DI/DO interfaces, Power Modules can collect and transfer data over power lines from power meters (or EVSE) and IoT devices to replace Ethernet cable wiring/unstable wireless connections of existing field applications. It enables significant cost savings on installation, maintenance and wiring materials.

The Power Module series works within an electric wire domain of up to 250 nodes; enabling large scale deployment, ideal for EV charging station (EVSE) backend communication, smart parking and data centers.

From an installation point of view, the Power Module design provides a terminal block (for power wire insert), mounting holes and a DIN rail mounting kit option.



KEY FEATURES

- Data and power on a single wire, reuses existing wiring
- Up to 250 nodes in one power group connection
- Up to 16 levels of repetition
- Reaches up to 700 meters in field tests
- Automatic Self-Healing - node to node will find the best path via software
- Plug and Play

PM-1540

GE LAN | RS-485 | DI/DO | Industrial IoT | ITU-T G.hn

SPECIFICATIONS

HARDWARE	
Model	PM-1540
Ethernet Port	4
Data In / Data Out	1
RS-485	1
DIN Rail Kit	Optional
*GIGABIT ETHERNET	
IEEE 802.3bz 10/100/1000 BASE-T, auto-sense Support MDI/MDX	
POWER LINE COMMUNICATION	
ITU-T G.9960 & G.9961 compliant G.hn 50MHz MIMO Boost	
MANAGEMENT	
HTTP Web-based (optional) TR-069 over IPv4/v6 dual stack (Optional)	
MODULATIONS	
OFDM, FEC	
DIMENSIONS	
PM-1540 115mm (H) x 65 mm (W) x 21 mm (PCB w/components) 120mm (H) x 70 mm (W) x 26.5 mm (with housing)	
ENVIRONMENT	
Temperature	Operating: -10°C ~ 65°C Storage: -25°C ~ 65°C (-13°F ~ 149°F)
Humidity (Non-condensing)	Operating: 10 ~ 90% RH, non-condensing Storage: 5 ~ 90% RH, non-condensing
ACCESSORY	
DIN Rail mounting kit (Optional)	



Warning

- . Disconnect the PLC from the power source before servicing
- . Do NOT open the casing
- . For indoor user only
- . Do NOT use near water

COMTREND

Taiwan:
3F-1, No.10, Lane 609, Chongxin Road, Section 5,
Sanchong Dist, New Taipei City 241405, Taiwan
Tel: +886-2-29998261

India:
446 Sector 8, IMT Manesar, Gurugram,
Haryana 122051, India
E-mail: India.admin@comtrend.com

USA & Canada:
530 Technology Dr, Suite 100, Irvine,
CA 92618, USA
Tel: +1-949-753-9640

Spain:
C/ Proci3n, 7 portal 2, 1º C - Edif. Am3rica II
28023 Madrid, Spain
Tel: 34-917990403

Czech Republic:
TOKOVO Jankovcova 1518/2, 170 00, Prague 7,
Czech Republic
Tel: +420-266-782040

Maximum performance, actual data rates, and coverage will vary depending on network conditions and environmental factors. Product specifications and design are subject to change without notice.