

Wi-Fi 7 10GEth. Router BE7200

802.11be | 4T5R-Dual-Band | BE7200 | VoIP | 10GE | TR-069

VG-8031u









Introducing the VG-8031u, a state of the art Wi-Fi 7 Router designed to transform your home or business network. Built on the advanced latest Airoha platform, it supports dual-band 802.11be, providing lightning-fast, reliable connectivity. With 10 Gigabit Ethernet WAN and LAN ports, 4 x Gigabit LAN ports, USB, and dual FxS ports, this router is the ultimate solution for high-performance networking. Whether you're streaming, gaming, or managing a smart home, the VG-8031u delivers unmatched speed, coverage, and versatility, ensuring your network is always a step ahead.

KEY FEATURES

- Cutting-Edge Dual-band Wi-Fi 7: Experience blazing-fast wireless connectivity with advanced 4T5R Dual-band Wi-Fi 7 technology, providing exceptional coverage and performance.
- 4096-QAM (4K-QAM): Enables each symbol to carry 12 bits rather than 10 bits, resulting in 20% higher theoretical transmission rates than Wi-Fi 6's 1024-QAM.
- 320MHz Bandwidth: Ultra-fast, high-capacity data transmission for seamless connectivity
- **Ultra-Fast 10GE Connectivity:** Enjoy lightning-fast internet speeds with 10 Gigabit Ethernet WAN and LAN ports for seamless online experiences.
- **Multi-Link Operation:** Enhanced performance by utilizing multiple links simultaneously for reduced latency.
- Multiple Resource Units: Efficiently allocates bandwidth to boost multi-device performance.

VG-8031u

802.11be | 4T5R-Dual-Band | BE7200 | VoIP | 10GE | TR-069

SPECIFICATIONS

| HARDWARE SPECIFICATIONS | |
|---------------------------|--|
| Main CPU | AN7581PT |
| Wi-Fi Chipset | Filogic 660 |
| Flash | 512MB |
| RAM | DDR4 512MB 16bit DDR4 |
| Interface | 1 x 10GE WAN Port + 1 x 10GE LAN Port + 4 x GE LAN Port, 1 x USB 3.0, 2 x FxS |
| Antenna | 9 internal antennas |
| Button | 1 x RESET. 1 x WPS/MESH. 1 x Wi-Fi/LED |
| LED | 8LED, POWER、WAN、NET、2.4G、5G、TEL1、TEL2、MESH |
| Power Requirement | DC: 12V / 3A |
| RF SPECIFICATIONS | |
| Wireless Standard | IEEE 802.11be/ax/ac/n/g/b/a @2.4GHz IEEE 802.11be/ax/ac/n/g/b/a @5GHz |
| Frequency Band | 2.4GHz (4x4), 5GHz (4x5) |
| ADVANCED FEATURES | |
| Wi-Fi Features | 320MHz bandwidth, 4096-QAM, MLO, MRU |
| Internet Protocol | IPv4, IPv6 |
| Wi-Fi Security | WPA-PSK, WPA2-PSK, WPA-PSK/ WPA2-PSK, WEP, WPA3-SAE, WPA2-PSK/WPA3-SAE |
| Management Function | Local GUI Management, TR-069 Remote Management |
| ENVIRONMENT & PHYSICAL | |
| Certification | CE, RoHS |
| Temperature Range | Operation: 0 to 40°C. Storage: -40 to 70°C |
| Humidity (non-condensing) | Relative Humidity: 5% to 90%. Storage Humidity: 5% to 95%. |

COMTREND

Taiwan: 3F-1, No.10, Lane 609, Chongxin Road, Section 5, Sanchong Dist, New Taipei City 241405, Taiwan Tel: 886-2-2999-8261

India: 446 Sector 8, IMT Manesar, Gurugram, Haryana 122051, India E-mail: India.admin@comtrend.com

USA & Canada:

530 Technology Dr. Suite 100 Irvine, CA 92618 USA Tel: (949)-753-964

Spain: Edif. América II C/Prócion,7 portal 3 bajo H 28023 Madrid, Spain Tel: 34-917990403

Czech Republic: TOKOVO Jankovcova 1518/2, 170 00, Prague 7, Czech Republic Tel: 420-266-782040